

RAY-BAR ENGINEERING CORPORATION

TECHNICAL DATA FOR FIREPLACE GLASS PANELS

Product Trade Name: NEOCERAM

PRODUCT DESCRIPTION:

A Clear Glass-Ceramic panel that is resistant to thermal shock and heat resistant nearly 3x more than that of standard tempered glass.

ATTENTION:

Please note the following points:

- 3/16" (5mm) thick clear silica coated Glass-Ceramic
 - Available cut to customer order size
 - Standard stock sizes up to 44" x 78" maximum
 - Excellent heat resistance
 - Withstands continuous temperatures up to 1292°F
 - Almost zero thermal expansion coefficient
 - This product is not UL listed or classified
 - This is not a Fire Rated Product
 - This product is not Fire Protective or Fire Resistive
 - This product is not impact resistant
-
- * For Fire Protective against flame and smoke or Fire Rated Glass utilize:
Ceramic Glass products: FireLite, FireLite+PLus or WireLite-NT (UL Listed)

 - * For Fire Resistive, Flame, Smoke, Radiant Heat and Conductive Heat Barrier utilize:
Pyrostop Glass (UL Listed)

RAY-BAR ENGINEERING CORPORATION

WWW.RAYBAR.COM

LIFE AND SAFETY PRODUCTS



• RADIATION • FIRE • BALLISTICS • BLAST •

PH: (800) 444-9729 E-MAIL: SALES@RAYBAR.COM FAX: (800) 333-9729

" WHEN PROTECTION IN REQUIRED, THERE IS NO SUBSTITUTE FOR SKILL AND EXPERIENCE "