

# RAY-BAR ENGINEERING CORPORATION

## TECHNICAL DATA FOR CLEAR TEMPERED 1/4" FIREGLASS® 20 RATED GLASS FOR DOOR ONLY

FOR INSTALLATION INTO DOOR VISION FRAME ONLY


20 MINUTE FIRE RATED SIZES IN MAXIMUM VISIBLE EXPOSED AREA VIEW LIMITS

Product Trade Name: FIREGLASS® 20 

It is the responsibility of the customer to verify and confirm fire rating requirement prior to ordering.

**20 MINUTE FIRE RATED FOR DOORS ONLY**

**WITHOUT HOSE STREAM TEST**



**ATTENTION: THIS PRODUCT IS FOR DOORS ONLY**

Please note the following points.

- UL Listed/Classified and permanently labeled for door assemblies 20 minute.
  - Very Clear and Affordable for 20 minute rated door vision glass applications.
  - Impact Safety Rated meeting ANSI Z97.1 and CPSC 16CFR1201 (Cat I and Cat II).
  - Tempered for Safety (4x stronger than wired glass).
  - This glass is for use in door vision frames only, and meets positive pressure UL 10C.
  - This glass is fire protective only and not a barrier to radiant heat.
  - This glass is not for wall windows and does not pass the Hose Stream Test.
  - Available in IGU for Low-E, Tinted, Reflective, 1-Way Mirror and X-Ray Protective.
  - Fireglass 20 has 89% visible light transmission.
  - UL File R13377, Testing to UL 9, UL 10B, UL 10C and NFPA 252 (WITHOUT HOSE STREAM TEST).
- 
- For larger size options or Higher Fire Ratings up to 90 minute with Hose Stream Testing and Impact Resistance utilize FireLite-NT, FireLite+Plus or WireLite-NT fire rated glass products.
  - For Fire Resistive, Radiant and Conductive Heat Barrier with Hose Stream Test utilize PILKINGTON PYROSTOP® Glass (Meeting ASTM E-119 and UL 263).

**RAY-BAR ENGINEERING CORPORATION**

**WWW.RAYBAR.COM**

**LIFE AND SAFETY PRODUCTS**



• **RADIATION • FIRE • BALLISTICS • BLAST •**

**PH: (800) 444-9729 E-MAIL: SALES@RAYBAR.COM FAX: (800) 333-9729**

**"WHEN PROTECTION IN REQUIRED, THERE IS NO SUBSTITUTE FOR SKILL AND EXPERIENCE"**

© 2019 Ray-Bar Engineering Corporation. \* Ray-Bar is a registered trademark of Ray-Bar Engineering Corp. \* FireLite and FireLite Plus are registered trademarks of NEG Co., Ltd.

\* Pilkington Pyrostop is a registered trademark of Pilkington plc. \* WireLite and Fireglass are registered trademarks of TGP. \* For additional information and details please contact Ray-Bar.